MATERIAL SAFETY DATA SHEET · MSDS





SECTION 1 • PRODUCT IDENTIFICATION

TRADE NAME **ABRASIVE WHEEL**

ANAMET PRODUCT NUMBER 114-X

CHEMICAL NAME

MANUFACTURER / SUPPLIER'S NAME **ANAMET ADDRESS**

P.O. Box 538

BOUCHERVILLE, QUÉBEC, J4B 6Y2

TELEPHONE NO. (450) 646-1290

EMERGENCY TELEPHONE NO. CANUTEC (613) 996-6666

SECTION II • COMPOSITION / INFORMATION ON COMPONENTS

Chemical characterization Description	CAS number	%	OSHA PEL (mg/m³)	ACGIH TLV (mg/m³)
Aluminum Oxide non Fibrous	1344-28-1	50-90	15.00	10.00
Zirconium oxide	1314-23-4	30-60	5	5
Silicon carbide.	409-21-2	30-75	10	10
Calcium oxide	1305-78-8	0-3	5	2
Cured phenolic resin	9003-35-4	6-20	Not available	Not available
Cured rubber	Not available	0-5	Not available	Not available
Fluorides (as F).	Not available**	1-10	2.50	2.50
Sulfur.	7704-34-9	1-8	Not available.	10.00
Red Iron Oxide.	1309-37-1	0-3	10.00	5.00
Sulphates	Not available	0-10	10	10

NOTE: Ingredients are listed on the TSCA Inventory of Chemical Substances. Those not identified are non-hazardous.

^{*}Materials are regulated by OSHA 29 CFR 1910.1200

^{**}Product is a compound and/or mixture.

^{***}Partially or completely hydrated during cure, becoming calcium hydroxide.

MATERIAL SAFETY DATA SHEET • MSDS





SECTION III •	PHYSICAL	CHEMICAL	CHARACTERISTICS
OLCHON III *	FILISICAL/	GIILIVIIGAL	UI IANAU I LNIO I IUO

Boiling point in °C	Not	Vapor pressure	Not
Boiling point in *C	applicable.	(mm Hg)	applicable.
Melting point in °C	Not	Vapor density (Air = 1)	Not
	available.		applicable.
Density	1.8-3	Evaporation rate	Not
(Water = 1)	1.0-3	(Butyl acetate= 1)	applicable.
Solubility in water	Insoluble.		
Appearance and odor	Solid, no odor when supplied.		

SECTION IV • FIRE / EXPLOSION HAZARD

Flash point	Product is non-flammable.			
Flammability Limits	LEL	Not applicable.	UEL	Not applicable.
Extinguishing media		foam, dry painers cool by		D ₂ . Keep fire water.
Special fire fighting procedures	·	ned breathing thing should be		
Unusual fire and explosion hazards	Carbon Mon- gases.	oxide, carbon	dioxide and	other irritant

SECTION V • *REACTIVITY*

Stability	Stable.
Incompatibility	Not available.
Hazardous decomposition products	None.
Hazardous Polymerization	Will not occur.

SECTION VI • TOXICOLOGICAL PROPERTIES OF PRODUCT

A - SUGGESTED FIRST AID

•	Irrigate with eyewash solution or clean water, holding the eyelids apart for at
	least 15 minutes. Obtain medical attention. Never give anything by mouth to an
	unconscious person. Call a physician.
Skin	Wash affected areas with soap and water. Obtain medical assistance.
	Remove patient from exposure, keep warm and at rest. Obtain immediate medical attention.

MATERIAL SAFETY DATA SHEET · MSDS





Ingestion Do not induce vomiting. Wash out mouth with water and give 200-300 ml (half a pint) of water to drink. Obtain medical attention. Never give anything by mouth to an unconscious person. Call a physician.

B – TOXICOLOGICAL INFORMATION

PRIMARY ENTRY ROUTES: Inhalation, ingestion, skin, and eye.		
▼ SHORT TERM EXPO	DSURE ▼	
Eyes	Dust may irritate eyes.	
Skin	Some may experience skin irritation from dust.	
Inhalation	Acute: coughing, shortness of breath.	
	Chronic: May affect breathing capacity.	
Ingestion	Not known to have adverse effects, but ingestion is not	
	recommended.	
Other potential health	Grinding may create elevated sound levels which may affect	
risks	hearing and may aggravate pre-existing respiratory conditions.	

▼ LONG TERM EXPOSURE ▼

Carcinogenicity	No ingredients listed by IARC, ACCGIH, NTP, and OSHA as a		
	carcinogen.		
Teratogenicity,	There is no reason to believe that this product represents a		
Mutagenicity and	significant mutagenic hazard to man based upon evidence from		
other reproductive	well conducted animal studies, relevant Mutagenicity studies, and		
effects	adequate epidemiology studies in relevant cohorts.		
Skin Sensitization	This product may cause skin sensitization (allergy).		
Respiratory tract sensitization	Not available.		
Synergistic materials	Not available.		

SECTION VII • PRECAUTIONARY INFORMATION PERSONAL PROTECTIVE MEASURES

Eye protection	Wear safety glasses. See OSHA 29 CFR 1910.33		
Respiratory protection	Respirators are required when airborne contaminant levels exceed		
	the TLV.		
Ventilation	Use adequate ventilation. See OSHA 29 CFR 1910.94 & 29 CFR		
	1910.1000		
Hearing	May create elevated sound levels. See OSHA 29 CFR 1910.134.		
	Hearing protection should be worn where required.		
Other precautions	See OSHA 29 CFR 1910.25.		
HMIS Hazard Ratings	Health: 1 Flammability: 0 Reactivity: 0		

MATERIAL SAFETY DATA SHEET · MSDS



SECTION VIII • SAFETY PRECAUTIONS IN CASE OF LEAKS OR SPILLS			
Spill or leak procedure	Clean up in standard manner.		
Waste disposal	Follow standard landfill methods consistent with federal, provincial		
	and municipal laws.		

SECTION IX • STORAGE AND HANDLING Storage Store in a cool well ventilated dry area. Handling • Always handle and store wheels in a careful manner. Always visually inspect all wheels before mounting. Always check machine speed against the established maximum safe operating speed marked on the wheel. Always check mounting flanges for equal and correct diameter. Always use mounting blotters on wheels for dry cutting. Always be sure work rest is properly adjusted. • Always use a safety guard covering at least one half of the grinding wheel. Always allow newly mounted wheels to run at operating speed, with guard in place, for at least one minute before grinding. • Always turn off coolant before stopping wheel to avoid creating an out-off balance wheel. Shipping Dot Shipping Name: Not regulated. classification TDG/UN Shipping Names: Not available. UN Number: Not available. Hazard Class: Not available. DOT **Hazard Class** Packing Group: Not available. TDG Exemption: Not available. Label: Not available. IATA Class: Not regulated. IMDG Class: Not regulated. **HMIS Coding** Health: 1 Flammability: 0 Reactivity: 0

SECTION X • *ECOLOGICAL INFORMATION*

Environmental Fate and Distribution	Insoluble in water.
Persistence and Degradation	Not readily biodegradable.
Toxicity	Not available.
Effect of effluent treatment	The product is substantially removed in biological
	treatment processes.

MATERIAL SAFETY DATA SHEET • MSDS



SECTION XI • REGULATORY INFORMATION

EC REGULATIONS:

TSCA STATUS: On Toxic Substance Control Inventory. CERCLA REPORTABLE QUANTITY: Not regulated.

SARA TITLE III

• Section 302: None.

Section 311/312 None.

Section 313: None.

RCRA STATUS: Not regulated.

CANADIAN REGULATIONS:

WHMIS Classification: Not regulated.

Anamet Inc. declines all warranties of description, merchantability or fitness for a particular purpose or any other warranties expressed or implied. All information contained in this data sheet result from figures supplied by the merchant and/or other recognized technical sources. Although this information is presumed to be complete and exact, Anamet Inc. does not guaranty any of the claims expressed or implied. Since the use of this product is not supervised by Anamet Inc., users are therefore responsible to verify if the product is designed for their particular application. They must also assume all risks associated with its use, manipulation and the elimination of the product as well as those arising from the publication, utilization or exactitude of the information contained in the present data sheet. This information pertains only of the product referred to in this specific data sheet and does not apply to its use in combination with other products or in any other process. In no event, Anamet Inc. will be liable for incidental or consequential damages resulting from the use or misuse of this product.



MATERIAL SAFETY DATA SHEET • MSDS

TERMINOLOGY

ACGIH: American Conference of Governmental Industrial Hygienists

CAS: Chemical Abstract Service

CFR: Code of Federal Regulations (Transportation in U.S.A.)

DOT: Department of Transportation (USA)

DSL: Domestic Substance List

HMIS: Hazardous material information sheet

IARC: International Agency for Research and Cancer

LC: Lethal Concentration

LD: Lethal Dosage

MSHA: Mine Safety and Health Administration (USA)

NIOSH: National Institute for Occupational Safety and Health (USA)

NTP: National Toxicology Program (U.S.A.)

OSHA: Occupational Safety and Health Administration (USA)

PEL: Permissible exposure limit.

STEL: Short term exposure limit.

TDG: Transportation of Dangerous Goods

TLV: Threshold limits value.

TSCA: Toxic Substances Control Act

TWA: Time-weighted average

USEPA: United States Environmental Protection Agency

WHMIS: Workplace Hazardous Materials Information System

Revised date: January 2015

SAFETY DATA SHEET / ABRASIVE WHEEL