MATERIAL SAFETY DATA SHEET . MSDS





SECTION 1 • PRODUCT IDENTIFICATION

TRADE NAME DIAMOND BLADE

ANAMET PRODUCT NUMBER 142M-X

CHEMICAL NAME

MANUFACTURER / SUPPLIER'S NAME ANAMET **ADDRESS** P.O. Box 538

BOUCHERVILLE, QUÉBEC, J4B 6Y2

TELEPHONE NO. (450) 646-1290

CANUTEC (613) 996-6666 **EMERGENCY TELEPHONE NO.**

SECTION II • COMPOSITION / INFORMATION ON COMPONENTS

Chemical characterization Description	CAS number	% max	OSHA PEL (mg/m³)	ACGIH TLV (mg/m³)
Diamond	7782-40-3	-	-	-
Copper	7440-50-8	<5	0.1	0.2

NOTE: Ingredients are listed on the TSCA Inventory of Chemical Substances. Those not identified are non-hazardous.

SECTION III • PHYSICAL / CHEMICAL CHARACTERISTICS

Boiling point in °C	Not applicable.	Vapor pressure (mm Hg)	Not applicable.
Melting point in °C	>240 °C (463°F)	Vapor density (Air = 1)	Not applicable.
Density (Water = 1)		Evaporation rate (Butyl acetate= 1)	Not applicable.
Solubility in water	Insoluble.		
Appearance and odor	Solid product. May give off an odor when in use.		

Revised date: January 2015 SAFETY DATA SHEET

Page 1 of 6

MATERIAL SAFETY DATA SHEET • MSDS





.3C(.11(.1)(.1)	SECTION IV	• FIRE	/ FXPI OSION	I HAZARD
-----------------	-------------------	--------	--------------	----------

Flash point	Not applica	ble		
Flammable limits	LEL	Not applicable.	UEL	Not applicable.
Extinguishing medium	Water.			_
Special fire fighting procedures	Not availab	le.		
Unusual fire and explosion hazards	None know	n.		

SECTION V • REACTIVITY

Stability	Stable.
Incompatibility	Not available.
Hazardous decomposition	When in use, decomposing odors are generated. In most
products	cases, the material removed from the work piece will be
	significantly greater than the grinding wheel components.
	Coolants may produce other decomposition products.
Hazardous Polymerization	Will not occur.
	

SECTION VI • TOXICOLOGICAL PROPERTIES OF PRODUCT

A - SUGGESTED FIRST AID

Eyes	Wash with large amounts of water. Obtain first aid and/or medical assistance if needed.
Skin	Wash affected areas with soap and water. Obtain medical assistance.
Inhalation	Remove to fresh air. Artificial respiration as needed and obtain medical assistance.
Ingestion	Obtain medical assistance.

B - TOXICOLOGICAL INFORMATION

PR	IMARY ENTRY ROUTES: Skin contact, inhalation and eye contact.			
 SHORT TERM 	SHORT TERM EXPOSURE			
Eyes	Dust may irritate eyes.			
Skin	Some may experience skin irritation from dust.			
Inhalation	ation Acute: coughing, shortness of breath.			
	Chronic: May affect breathing capacity.			
Ingestion	Not known to have adverse effects, but ingestion is not recommended.			
LONG TERM EXPOSURE				
Carcinogenicity	None.			

Revised date: January 2015 SAFETY DATA SHEET





Teratogenicity, Mutagenicity and other reproductive effects	None.
Skin Sensitization	None.
Respiratory tract sensitization	None.
Synergistic materials	None.

SECTION VII • PRECAUTIONARY INFORMATION PERSONAL PROTECTIVE MEASURES

Eye protection	Wear safety glasses. See OSHA 29 CFR 1910.33
Respiratory	Respirators are required when airborne contaminant levels exceed the
protection	TLV.
Ventilation	Use adequate ventilation. See OSHA 29 CFR 1910.94 & 29 CFR 1910.1000
Others	See OSHA 29 CFR 1910.25.
HMIS Ratings	Health: 1 Flammability: 0 Reactivity: 0

SECTION VIII • SAFETY PRECAUTIONS IN CASE OF LEAKS OR SPILLS

Spill or leak procedure	ocedure Clean up in standard manner.		
Waste disposal	Follow standard landfill methods consistent with federal, provincial		
	and municipal laws.		

SECTION IX • STORAGE AND HANDLING

SECTION IX •	STORAGE AND HANDLING
Storage	Store in cool, well ventilated dry area.
Handling	Always handle and store wheels in a careful manner.
_	 Always visually inspect all wheels before mounting.
	 Always check machine speed against the established maximum safe operating speed marked on the wheel.
	 Always check mounting flanges for equal and correct diameter.
	 Always use mounting blotters on wheels for dry cutting.
	 Always be sure work rest is properly adjusted.
	 Always use a safety guard covering at least one half of the grinding wheel.
	 Always allow newly mounted wheels to run at operating speed, with guard in place, for at least one minute before grinding.
	 Always turn off coolant before stopping wheel to avoid creating an out- off balance wheel.
Shipping classif	ication • Dot Shipping Name: Not regulated.

Revised date: January 2015 SAFETY DATA SHEET





DOT hazard class	 TDG/UN Shipping Names: Not regulated. UN Number: Not regulated.
	 Hazard Class: Not regulated.
	Packing Group: Not regulated.
	 TDG Exemption: Not regulated.
	Label: Not regulated.
	ATA Class: Not regulated.
	IMDG Class: Not regulated.
HMIS Coding	Health: 1 Flammability: 0 Reactivity: 0

SECTION X • ECOLOGICAL INFORMATION

Environmental Fate and Distribution	Not available.
Persistence and Degradation	Not available.
Toxicity	Not available.
Effect of effluent	Not available.
treatment	

SECTION XI • REGULATORY INFORMATION

• EC REGULATIONS:

TSCA STATUS: On Toxic Substance Control Inventory.

CERCLA REPORTABLE QUANTITY: None.

SARA TITLE III

• Section 302: None.

• Section 311/312: None.

• Section 313: Copper.

RCRA STATUS: Not regulated.

CANADIAN REGULATIONS:

WHMIS Classification: Not regulated.

Revised date: January 2015 SAFETY DATA SHEET

MATERIAL SAFETY DATA SHEET · MSDS





Anamet Inc. declines all warranties of description, merchantability or fitness for a particular purpose or any other warranties expressed or implied. All information contained in this data sheet result from figures supplied by the merchant and/or other recognized technical sources. Although this information is presumed to be complete and exact, Anamet Inc. does not quaranty any of the claims expressed or implied. Since the use of this product is not supervised by Anamet Inc., users are therefore responsible to verify if the product is designed for their particular application. They must also assume all risks associated with its use, manipulation and the elimination of the product as well as those arising from the publication, utilization or exactitude of the information contained in the present data sheet. information pertains only of the product referred to in this specific data sheet and does not apply to its use in combination with other products or in any other process. In no event Anamet Inc. will be liable for incidental or consequential damages resulting from the use or misuse of this product.

Revised date: January 2015 SAFETY DATA SHEET

Page 5 of 6



TERMINOLOGY

ACGIH: American Conference of Governmental Industrial Hygienists

CAS: Chemical Abstract Service

CFR: Code of Federal Regulations (Transportation in U.S.A.)

DOT: Department of Transportation (USA)

DSL: Domestic Substance List

IARC: International Agency for Research and Cancer

LC: Lethal Concentration

LD: Lethal Dosage

MSHA: Mine Safety and Health Administration (USA)

NIOSH: National Institute for Occupational Safety and Health (USA)

NTP: National Toxicology Program (U.S.A.)

OSHA: Occupational Safety and Health Administration (USA)

PEL: Permissible exposure limit.

STEL: Short term exposure limit.

TDG: Transportation of Dangerous Goods

TLV: Threshold limits value.

TSCA: Toxic Substances Control Act

TWA: Time-weighted average

USEPA: United States Environmental Protection Agency

WHMIS: Workplace Hazardous Materials Information System

Revised date: January 2015 SAFETY DATA SHEET

Page 6 of 6