

SECTION 1 • PRODUCT IDENTIFICATION

TRADE NAME	ABRASIVE WHEEL
ANAMET PRODUCT NUMBER	148-X
CHEMICAL NAME	

MANUFACTURER / SUPPLIER'S NAME ADDRESS

TELEPHONE NO. EMERGENCY TELEPHONE NO. ANAMET P.O. Box 538 BOUCHERVILLE, QUÉBEC, J4B 6Y2 (450) 646-1290 CANUTEC (613) 996-6666

SECTION II • COMPOSITION / INFORMATION ON COMPONENTS

Chemical characterization Description	CAS number	%	OSHA PEL (mg/m ³)	ACGIH TLV (mg/m ³)
Fused Aluminum Oxide.	1344-28-1	48-92	15.00	10.00
Silicon carbide.	409-21-2	48-92	15.00	10.00
Fluorides (as F).	Not available**	8-24	2.50	2.50
Sulfur.	7704-34-9	1-8	Not available.	10.00
Red Iron Oxide.	1309-37-1	2-10	10.00	5.00
Calcium oxide***	1305-78-8	0-1	5.00	2.00
NOTE: Ingredients are lis	sted on the TSCA I	nventory of C	hemical Substance	s. Those not

identified are non-hazardous.

*Materials are regulated by OSHA 29 CFR 1910.1200

**Product is a compound and/or mixture.

***Partially or completely hydrated during cure, becoming calcium hydroxide.

SECTION III • PHYSICAL / CHEMICAL CHARACTERISTICS

Boiling point in °C	Not	Vapor pressure	Not
	applicable.	(mm Hg)	applicable.
Melting point in °C	Not	Vapor density (Air = 1)	Not
	available.		applicable.
Density	2-3	Evaporation rate	Not
(Water = 1)	2-3	(Butyl acetate= 1)	applicable.
Solubility in water	Insoluble.		
Appearance and odor	Solid, no odor v	when supplied. Typical rubb	er odor when in use.

SECTION IV • *FIRE / EXPLOSION HAZARD*

Flash point	Product is non-flammable.			
Flammability Limits	LEL	Not applicable.	UEL	Not applicable.
Extinguishing media	Water spray, exposed contained			
Special fire fighting procedures	A self-contai protective clot			
Unusual fire and explosion hazards	Carbon Mono gases.	oxide, carbon	dioxide and	other irritant

SECTION V • REACTIVITY

Stability	Stable.
Incompatibility	Not available.
Hazardous decomposition products	None.
Hazardous Polymerization	Will not occur.

SECTION VI • TOXICOLOGICAL PROPERTIES OF PRODUCT A - SUGGESTED FIRST AID

Eyes	Irrigate with eyewash solution or clean water, holding the eyelids apart for at least 15 minutes. Obtain medical attention. Never give anything by mouth to an unconscious person. Call a physician.
Skin	Wash affected areas with soap and water. Obtain medical assistance.
Inhalation	Remove patient from exposure, keep warm and at rest. Obtain immediate medical attention.
Ingestion	Do not induce vomiting. Wash out mouth with water and give 200-300 ml (half a pint) of water to drink. Obtain medical attention. Never give anything by mouth to an unconscious person. Call a physician.

B – TOXICOLOGICAL INFORMATION

	PRIMARY ENTRY ROUTES: Inhalation, ingestion, skin, and eye.
▼ SHORT	TERM EXPOSURE V
Eyes	Dust may irritate eyes.
Skin	Some may experience skin irritation from dust.
Inhalation	Acute: coughing, shortness of breath.
	Chronic: May affect breathing capacity.
Ingestion	Not known to have adverse effects, but ingestion is not recommended.



Other G	rinding may create elevated sound levels which may affect hearing and may
potential ag	gravate pre-existing respiratory conditions.
health risks	
▼ LONG TERM	MEXPOSURE V
Carcinogenicit	y No ingredients listed by IARC, ACCGIH, NTP, and OSHA as a carcinogen.
Teratogenicity, Mutagenicity and other reproduce effects	nd significant mutagenic hazard to man based upon evidence from
Skin Sensitizat	ion This product may cause skin sensitization (allergy).
Respiratory tra sensitization	ct Not available.
Synergistic ma	terials Not available.

SECTION VII • PRECAUTIONARY INFORMATION

PERSONAL PROTECTI	VE MEASURES
Eye protection	Wear safety glasses. See OSHA 29 CFR 1910.33
Respiratory protection	Respirators are required when airborne contaminant levels exceed the TLV.
Ventilation	Use adequate ventilation. See OSHA 29 CFR 1910.94 & 29 CFR 1910.1000
Hearing	May create elevated sound levels. See OSHA 29 CFR 1910.134. Hearing protection should be worn where required.
Other precautions	See OSHA 29 CFR 1910.25.
HMIS Hazard Ratings	Health: 1 Flammability: 0 Reactivity: 0

SECTION VIII • SAFETY PRECAUTIONS IN CASE OF LEAKS OR SPILLS

Spill or leak procedureClean up in standard manner.Waste disposalFollow standard landfill methods consistent with federal, provincial
and municipal laws.



SECTION IX • STORAGE AND HANDLING

StorageStore in a cool well ventilated dry area.Handling• Always handle and store wheels in a careful manner. • Always visually inspect all wheels before mounting. • Always check machine speed against the established maximum safe operating speed marked on the wheel. • Always check mounting flanges for equal and correct diameter. • Always use mounting blotters on wheels for dry cutting. • Always be sure work rest is properly adjusted. • Always use a safety guard covering at least one half of the grinding wheel. • Always allow newly mounted wheels to run at operating speed, with guard in place, for at least one minute before grinding.
 Always visually inspect all wheels before mounting. Always check machine speed against the established maximum safe operating speed marked on the wheel. Always check mounting flanges for equal and correct diameter. Always use mounting blotters on wheels for dry cutting. Always be sure work rest is properly adjusted. Always use a safety guard covering at least one half of the grinding wheel. Always allow newly mounted wheels to run at operating speed, with guard in
 Always check machine speed against the established maximum safe operating speed marked on the wheel. Always check mounting flanges for equal and correct diameter. Always use mounting blotters on wheels for dry cutting. Always be sure work rest is properly adjusted. Always use a safety guard covering at least one half of the grinding wheel. Always allow newly mounted wheels to run at operating speed, with guard in
 speed marked on the wheel. Always check mounting flanges for equal and correct diameter. Always use mounting blotters on wheels for dry cutting. Always be sure work rest is properly adjusted. Always use a safety guard covering at least one half of the grinding wheel. Always allow newly mounted wheels to run at operating speed, with guard in
 Always use mounting blotters on wheels for dry cutting. Always be sure work rest is properly adjusted. Always use a safety guard covering at least one half of the grinding wheel. Always allow newly mounted wheels to run at operating speed, with guard in
 Always be sure work rest is properly adjusted. Always use a safety guard covering at least one half of the grinding wheel. Always allow newly mounted wheels to run at operating speed, with guard in
 Always use a safety guard covering at least one half of the grinding wheel. Always allow newly mounted wheels to run at operating speed, with guard in
 Always allow newly mounted wheels to run at operating speed, with guard in
place, for at least one minute before grinding.
 Always turn off coolant before stopping wheel to avoid creating an out-off balan
wheel.
 Shipping Dot Shipping Name: Not regulated.
 TDG/UN Shipping Names: Not Available.
UN Number: Not Available.
• Hazard Class: Not Available.
Hazard Class • Packing Group: Not Available.
TDG Exemption: Not Available.
Label: Not Available.
 IATA Class: Not regulated.
IMDG Class: Not regulated.
HMIS Coding Health: 1 Flammability: 0 Reactivity: 0

SECTION X • ECOLOGICAL INFORMATION

Environmental Fate and Distribution	Insoluble in water.
Persistence and Degradation	Not readily biodegradable.
Toxicity	Not available.
Effect of effluent treatment	The product is substantially removed in
	biological treatment processes.



	A STATUS: On Toxic Substance Co	
CER	CLA REPORTABLE QUANTITY: Not	regulated.
SAR	A TITLE III	
•	Section 302: None.	
•	Section 311/312: None.	
•	Section 313: None.	
RCR	A STATUS: Not regulated.	
	<u> </u>	
CANADI/	AN REGULATIONS:	

Anamet Inc. declines all warranties of description, merchantability or fitness for a particular purpose or any other warranties expressed or implied. All information contained in this data sheet result from figures supplied by the merchant and/or other recognized technical sources. Although this information is presumed to be complete and exact, Anamet Inc. does not guaranty any of the claims expressed or implied. Since the use of this product is not supervised by Anamet Inc., users are therefore responsible to verify if the product is designed for their particular application. They must also assume all risks associated with its use, manipulation and the elimination of the product as well as those arising from the publication, utilization or exactitude of the information contained in this specific data sheet. This information pertains only of the product referred to in this specific data sheet and does not apply to its use in combination with other products or in any other process. In no event, Anamet Inc. will be liable for incidental or consequential damages resulting from the use or misuse of this product.



TERMINOLOGY

- ACGIH: American Conference of Governmental Industrial Hygienists
- CAS: Chemical Abstract Service
- CFR: Code of Federal Regulations (Transportation in U.S.A.)
- **DOT:** Department of Transportation (USA)
- DSL: Domestic Substance List
- HMIS: Hazardous material information sheet
- IARC: International Agency for Research and Cancer
- LC: Lethal Concentration
- LD: Lethal Dosage
- MSHA: Mine Safety and Health Administration (USA)
- NIOSH: National Institute for Occupational Safety and Health (USA)
- NTP: National Toxicology Program (U.S.A.)
- **OSHA:** Occupational Safety and Health Administration (USA)
- PEL: Permissible exposure limit.
- **STEL:** Short term exposure limit.
- TDG: Transportation of Dangerous Goods
- TLV: Threshold limits value.
- TSCA: Toxic Substances Control Act
- **TWA:** Time-weighted average
- **USEPA:** United States Environmental Protection Agency
- WHMIS: Workplace Hazardous Materials Information System