

# MATERIAL SAFETY DATA SHEET • MSDS



## SECTION 1 • PRODUCT IDENTIFICATION

<b>TRADE NAME</b>	<b>PHENOLIC PREFORMS</b>
<b>ANAMET PRODUCT NUMBER</b>	<b>201-X-X</b>

### CHEMICAL NAME

**MANUFACTURER / SUPPLIER'S NAME** ANAMET  
**ADDRESS** P.O. Box 538  
 BOUCHERVILLE, QUÉBEC, J4B 6Y2  
**TELEPHONE NO.** (450) 646-1290  
**EMERGENCY TELEPHONE NO.** CANUTEC (613)-996-6666

## SECTION II • COMPOSITION / INFORMATION ON COMPONENTS

Chemical characterization Description	CAS number	%	OSHA PEL (mg/m <sup>3</sup> )	ACGIH TLV (mg/m <sup>3</sup> )
Phenol.	108-95-2	< 6.3	5	5
Formaldehyde.	50-00-0	<0.6	0.75	0.3
Carbon black.	1333-86-4	< 12	3.5	3.5
Coal dust.		< 18	2.4	2
Talc.	14807-96-6	< 20	20	2
Graphite.	7782-42-5	<40	15	2
Particulates not otherwise classified (PNOC).		< 70	5	3
Mica	12001-26-2	< 60	20	3

**NOTE:** Ingredients are listed on the TSCA Inventory of Chemical Substances. Those not identified are non-hazardous.

Unless specifically indicated otherwise, the following information applies to the compound in the form sold, not to articles, parts, etc. molded of the compound; in normal molding, the material substantially completes its progression to a cross-linked insoluble, infusible solid.

## SECTION III • PHYSICAL / CHEMICAL CHARACTERISTICS

<b>Boiling point in °C</b>	Not available	<b>Vapor pressure (mm Hg)</b>	Not available.
<b>Melting point in °C</b>	Not available	<b>Vapor density (Air = 1)</b>	Not available.
<b>Density (Water = 1)</b>	1.83.	<b>Evaporation rate (Butyl acetate= 1)</b>	Not available.
<b>Solubility in water</b>	Negligible		
<b>Appearance &amp; odor</b>	Solid powder with slight odor of phenol.		

# MATERIAL SAFETY DATA SHEET • MSDS



## SECTION IV • FIRE / EXPLOSION HAZARD

<b>Flash point (Test Method)</b>	Non flammable		
<b>Flammable Limits</b>	<b>LOWER</b>	0.03oz./pcf	<b>UPPER</b> Not determined.
<b>Extinguishing medium</b>	Water fog, foam, dry chemical, carbon dioxide.		
<b>Special fire fighting procedures</b>	MSHA/NIOSH approved self-contained breathing apparatus recommended. Avoid inhalation of gases.		
<b>Unusual fire and explosion hazards</b>	Organic dust/air mixtures are highly flammable (explosive); avoid dust accumulations or dust-laden atmospheres and sources of ignition.		

## SECTION V • REACTIVITY

<b>Stability</b>	Stable. Avoid contamination, exposure to flame or heat, or storage at temperatures in excess of 100 <sup>0</sup> F.
<b>Incompatibility</b>	Like most organic materials, this product is sensitive to strong oxidizing agents and may either decompose or ignite when mixed with same.
<b>Hazardous Decomposition Products</b>	Vapors evolved during polymerization may contain phenol, formaldehyde, or ammonia.
<b>Hazardous polymerization</b>	Should not occur.

## SECTION VI • TOXICOLOGICAL PROPERTIES OF PRODUCT

### A - SUGGESTED FIRST AID

<b>Eyes</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
<b>Skin</b>	Wash thoroughly with soap and water.
<b>Inhalation</b>	Use with adequate ventilation. If breathing is affected, remove to fresh air. If breathing stops, apply mouth to mouth resuscitation. Get medical attention
<b>Ingestion</b>	If conscious, give water immediately. Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention.
<b>Health hazard data</b>	However, "as sold" the plastic resin is not completely "cured" or reacted and contains some non-reacted ingredients dissolved within it. So dissolved, these chemicals are extremely unlikely to pose a hazard; but because they are hazardous in their pure forma, OSHA requires that they be reported and described as hazardous ingredients (see below and Section VI-B). Under normal conditions of storage and handling, no significant amounts of hazardous vapors should evolve from the "as sold" product. Because phenol is more soluble in the resin than in water, there is no liquefying significant health hazard



through skin absorption. The great majority of filling materials are imbedded within compound granules that are large enough not to constitute an inhalation hazard. Nevertheless, some particles of plastic resin and/or filling materials may be present in a size that constitutes a Respirable dust (including, in some products, up to 1% inorganic filling material mixed in after compounding). This Respirable dust may contain one or more of the following materials: carbon black, coal dust, fibrous glass, graphite, mica, mineral wool fiber, talc, and/or wood floor (soft). Chronic inhalation of each of the above has been associated with fibrotic lung disease. For most of all, it has been associated with increased risk of lung cancer, especially among smokers. Inhalation of dust should be avoidable with proper material handling procedures and good ventilation, but if not, respirators should be worn. The primary acute health risk from exposure to the product "as sold" is irritation, especially from the dust. Ingestion, inhalation of dust, and contact with skin and eyes should be avoided.

**As used:**

During polymerization (e.g., curing of the product during normal processing) or decomposition (e.g., overheating or burning of the product) small amount of gaseous ammonia, phenol and formaldehyde (as well as water vapor, carbon monoxide and carbon dioxide) are evolved. Breathing of the fumes can be harmful. If the odor of ammonia or formaldehyde is noticeable, then the airborne concentration of those chemicals should be carefully monitored and ventilation improvements considered; those chemicals begin to be detectable by odor at concentrations approaching or exceeding the PELs. The odor of phenol begins to be noticeable at a concentration about one-fifth the PEL. In any case, adequacy of ventilation can best be determined by use of instruments to monitor airborne concentrations of ammonia, phenol, and formaldehyde. Grinding or machining of cured molded material may create a dust that poses a respiratory hazard if inhaled (see above) and may release small amounts of gaseous ammonia.

**B – TOXICOLOGICAL INFORMATION**

**PRIMARY ENTRY ROUTES:** Skin contact, inhalation and eye contact.

• **LONG TERM EXPOSURE**

Ordinary use of this product is unlikely to produce significant exposure to hazardous chemicals. PELs for these chemicals are set at levels designed to avoid any significant health risk and are achievable with proper material handling procedures, ventilation and housekeeping. Nevertheless, per OSHA requirement, we list the following possible health hazards if one were exposed to the following chemicals at levels much higher, or in a different form, than expected from ordinary use of this product.

<ul style="list-style-type: none"> <li>• Phenol</li> </ul>	Highly toxic. Poisoning may occur via skin absorption, vapor inhalation, or ingestion. Inhalation of the vapors may cause severe irritation to the nose, throat, and respiratory tract. May cause liver, kidney and heart damage.
<ul style="list-style-type: none"> <li>• Formaldehyde</li> </ul>	Irritant to eyes, lungs and skin. Has been shown to cause cancer in laboratory animals. Listed as an IARC carcinogen. California law requires the following statement be included: contains a chemical (formaldehyde) known to the state of California to cause cancer. National cancer institute study finds

# MATERIAL SAFETY DATA SHEET • MSDS



	little evidence to connect formaldehyde exposure with cancer in humans. May cause respiratory sensitization.
• Ammonia	Irritant to eyes, mucous membranes and respiratory tract. Possible Respirable dust components (up to 8% may go through 100 meshes).
• Carbon black	Irritant to eyes and respiratory tracts. Exposures at high levels are associated with declines in pulmonary function and cardio vascular stress.
• Coal dust	Irritant to eyes, nose and throat. May cause respiratory effects such as pneumoconiosis, bronchitis, emphysema and progressive massive fibrosis, with long exposure.
• Mineral wool fiber	Irritant to eyes and skin. Several studies have shown excess risk of non malignant respiratory disease.
• Talc	Irritant to eyes, mucous membranes and respiratory tracts. Medical evidence is complicated by the fact that talc contains amphiboles and other minerals.
• Wood flour (soft)	Irritant to eyes, mucous membranes and upper respiratory tracts. Various species of wood dust can elicit allergic contact dermatitis in sensitized individuals. May cause respiratory sensitization.
<b>Carcinogenicity</b>	Phenol and formaldehyde may cause cancer.
<b>Teratogenicity, Mutagenicity and other reproductive effects</b>	No Information
<b>Skin Sensitization</b>	May be irritating to the skin.
<b>Respiratory tract sensitization</b>	May be irritating to the respiratory tract.
<b>Synergistic materials</b>	No information.

## SECTION VII • PRECAUTIONARY INFORMATION

### PERSONAL PROTECTIVE MEASURES

<b>Eye , face &amp; hands</b>	Recommend standard face and eye protection at all times while using the product. Gloves are recommended.
<b>Respiratory protection</b>	As needed, use approved dust respirator (OSHA CFR1910.134).
<b>Ventilation</b>	Point source exhaust recommended removing dust and vapors evolved during use (dust collection system). Use explosion proof motors.
<b>Hearing</b>	As needed in accordance with OSHA 1910-215.
<b>HMIS Ratings</b>	Health: 2 Flammability: 1 Reactivity: 0

# MATERIAL SAFETY DATA SHEET • MSDS



## SECTION VIII • SAFETY PRECAUTIONS IN CASE OF LEAKS OR SPILLS

<b>Spill or leak procedure</b>	Vacuum or sweep with sweeping compound, sawdust or sand. Avoid generating dust. Vacuums with explosion proof motors are recommended. This product contains free phenol which is subject to effluent limits under the clean water act.
<b>Waste disposal</b>	Disposal should be in accordance with local, state, or national legislation. Incinerate under approved controlled conditions.

## SECTION IX • STORAGE AND HANDLING

<b>Storage</b>	Store in a cool, dry place. Keep containers closed to avoid Contamination. Prevent accumulations of dust. Avoid excessive heat and sources of ignition. Observe good housekeeping practices.
<b>Handling</b>	Prevent accumulations of dust. Avoid excessive heat and sources of ignition.
<b>Shipping Classification</b>	<ul style="list-style-type: none"> <li>• <b>Dot Shipping Name:</b> Not regulated for transport.</li> <li>• <b>TDG/UN Shipping Names:</b> None</li> <li>• <b>UN Number:</b> None</li> <li>• <b>Hazard Class:</b> None</li> <li>• <b>Packing Group:</b> None</li> <li>• <b>TDG Exemption:</b> None</li> <li>• <b>Label:</b> None</li> <li>• <b>IATA Class:</b> None</li> <li>• <b>IMDG Class:</b> None</li> </ul>
<b>DOT Hazard class</b>	
<b>HMIS Ratings</b>	Health: 2 Flammability: 1 Reactivity: 0

## SECTION X • ECOLOGICAL INFORMATION

<b>Environmental Fate and Distribution</b>	Not relevant.
<b>Persistence and Degradation</b>	Not relevant.
<b>Toxicity</b>	Not relevant.
<b>Effect of effluent treatment</b>	Not relevant.

## SECTION XI • REGULATORY INFORMATION

<b>• EC REGULATIONS:</b>	
--------------------------	--

# MATERIAL SAFETY DATA SHEET • MSDS



TSCA STATUS: None

SARA TITLE III

- Section 302: None.
- Section 311/312: None.
- Section 313: None.
- RCRA STATUS: None.

## • CANADIAN REGULATIONS:

WHMIS Classification: D2A

Anamet Inc. declines all warranties of description, merchantability or fitness for a particular purpose or any other warranties expressed or implied. All information contained in this data sheet result from figures supplied by the merchant and/or other recognized technical sources. Although this information is presumed to be complete and exact, Anamet Inc. does not guaranty any of the claims expressed or implied. Since the use of this product is not supervised by Anamet Inc., users are therefore responsible to verify if the product is designed for their particular application. They must also assume all risks associated with its use, manipulation and the elimination of the product as well as those arising from the publication, utilization or exactitude of the information contained in the present data sheet. This information pertains only of the product referred to in this specific data sheet and does not apply to its use in combination with other products or in any other process. In no event, Anamet Inc. will be liable for incidental or consequential damages resulting from the use or misuse of this product.



## TERMINOLOGY

**ACGIH:** American Conference of Governmental Industrial Hygienists

**CAS:** Chemical Abstract Service

**CFR:** Code of Federal Regulations (Transportation in U.S.A.)

**DOT:** Department of Transportation (USA)

**DSL:** Domestic Substance List

**IARC:** International Agency for Research and Cancer

**LC:** Lethal Concentration

**LD:** Lethal Dosage

**MSHA:** Mine Safety and Health Administration (USA)

**NIOSH:** National Institute for Occupational Safety and Health (USA)

**NTP:** National Toxicology Program (U.S.A.)

**OSHA:** Occupational Safety and Health Administration (USA)

**PEL:** Permissible exposure limit.

**STEL:** Short term exposure limit.

**TDG:** Transportation of Dangerous Goods

**TLV:** Threshold limits value.

**TSCA:** Toxic Substances Control Act

**TWA:** Time-weighted average

**USEPA:** United States Environmental Protection Agency

**WHMIS:** Workplace Hazardous Materials Information System