

MATERIAL SAFETY DATA SHEET • MSDS



SECTION 1 • PRODUCT IDENTIFICATION

| | |
|------------------------------|---------------------------------|
| TRADE NAME | TECHNOVIT 4006, HARDENER |
| ANAMET PRODUCT NUMBER | 234-H |

CHEMICAL NAME

| | |
|---------------------------------------|---|
| MANUFACTURER / SUPPLIER'S NAME | ANAMET |
| ADDRESS | P.O. Box 538 BOUCHERVILLE, QUÉBEC, J4B 6Y2 |
| TELEPHONE NO. | (450) 646-1290 |
| EMERGENCY TELEPHONE NO. | CANUTEC (613)-996-6666 |

SECTION II • COMPOSITION / INFORMATION ON COMPONENTS

| Chemical characterization Description | CAS number | % | OSHA PEL (mg/m ³) | ACGIH TLV (mg/m ³) |
|--|------------|------|-------------------------------------|--------------------------------------|
| Methyl Methacrylate. | 80-62-6 | >90 | 410 | 410 |
| Methacrylic Acid | 79-41-4 | 0-5% | Not available. | Not available. |

NOTE: Ingredients are listed on the TSCA Inventory of Chemical Substances. Those not identified are non-hazardous.

SECTION III • PHYSICAL / CHEMICAL CHARACTERISTICS

| | | | |
|--------------------------------|---|--|---|
| Boiling point in °C | 100 °C (200°F) | Vapor pressure (mm Hg) | 40mbar @ 20 °C (68°F). 64mbar @ 30 °C (86°F). 05mbar @ 40 °C (104°F). |
| Melting point in °C | Not determined. | Vapor density (Air = 1) | Not available. |
| Density (Water = 1) | 0.95 | Evaporation rate (Butyl acetate= 1) | Not available. |
| Solubility in water | Insoluble | | |
| Appearance and odor | Colorless liquid / Characteristic odor. | | |



SECTION IV • FIRE / EXPLOSION HAZARD

| | | | |
|---|---|------|-------------------|
| Flash point | Approx. 10 °C (50°F). | | |
| Flammable limits | LEL | 2.1% | UEL 12.5 % |
| Extinguishing media | Carbon dioxide, extinguishing powder, alcohol foam. Do not use water or water jet. | | |
| Special fire fighting procedures | MSHA/NIOSH approved self-contained breathing apparatus recommended and suitable protective clothing should be worn in fire conditions. Keep fire exposed containers cool by spraying water. | | |
| Unusual fire and explosion hazards | Formation of toxic gases is possible during heating or in case of fire. | | |

SECTION V • REACTIVITY

| | |
|---|--|
| Stability | Stable. |
| Conditions to avoid | No decomposition if used and stored according to specification |
| Incompatibility | Avoid bases, acids and oxidizing agents. |
| Hazardous decomposition products | Carbon monoxide and carbon dioxide. |
| Hazardous Polymerization | If stored longer than recommended and /or recommended temperature, product may polymerize generating heat. |

SECTION VI • TOXICOLOGICAL PROPERTIES OF PRODUCT

A - SUGGESTED FIRST AID

| | |
|-------------------|---|
| Eyes | Irrigate with eyewash solution or clean water, holding the eyelids apart for at least 20 minutes. Obtain medical attention. |
| Skin | Remove contaminated clothing. Wash skin immediately with water and soap for at least 20 minutes. If symptoms (irritation or blistering) occur obtain medical attention. |
| Inhalation | Remove patient from exposure, keep warm and at rest. Obtain immediate medical attention. |
| Ingestion | Do not induce vomiting. Obtain medical attention immediately. Symptoms of poisoning may even occur after several hours: therefore medical observation for at least 48 hours after the accident. |

MATERIAL SAFETY DATA SHEET • MSDS



B – TOXICOLOGICAL INFORMATION

PRIMARY ENTRY ROUTES: Inhalation, ingestion, skin, and eye contact.

• SHORT TERM EXPOSURE

| | |
|-------------------|---|
| Inhalation | Vapor or mist can irritate the nose, throat and lungs. Symptoms such as sore throat, coughing, chest pain, shortness of breath and difficult breathing may occur. |
| Skin | Liquid or vapor can irritate the skin. |
| Eyes | Liquid or high concentrations of vapor or mist can cause severe eye irritation. |
| Ingestion | Liquid may cause burning of the mouth, throat and digestive tract with abdominal pain, nausea, vomiting, diarrhea, thirst, weakness, shock (collapse) and death. Permanent damage could result. |

• LONG TERM EXPOSURE

| | |
|--|--|
| Carcinogenicity | Not established. |
| Teratogenicity, Mutagenicity and other reproductive effects | Not available. |
| Skin Sensitization | The product is a skin sensitization (allergy). |
| Respiratory tract sensitization | Respiratory sensitizer. |
| Synergistic materials | Not available |

SECTION VII • PRECAUTIONARY INFORMATION

PERSONAL PROTECTION MEASURES

| | |
|-------------------------------|---|
| Eye, face & hands | Safety spectacles/Full Face Shield. Wear suitable impervious (Neoprene) gloves. Gloves should be changed regularly and if excessive exposure has occurred. |
| Respiratory protection | Wear suitable respiratory protective equipment if exposure to levels above the occupational exposure limit is likely. A suitable mask with filter may be appropriate. In the event of formation of particularly high levels of vapor a self-contained breathing apparatus may be appropriate. |
| Ventilation | Provide adequate ventilation, including appropriate local extraction, to insure that the defined occupational exposure limit is not exceeded. Consideration should be given to the work procedures involved and the potential extent of exposure as they may determine whether a higher level of protection is required. |
| Hearing | As needed in accordance with OSHA 1910-215 |
| HMIS Coding | Health: 2 Flammability: 3 Reactivity: 2 |

MATERIAL SAFETY DATA SHEET • MSDS



SECTION VIII • SAFETY PRECAUTIONS IN CASE OF LEAKS OR SPILLS

| | |
|--------------------------------|---|
| Spill or leak procedure | Eliminate sources of ignition. Ensure suitable personal protection (including respiratory protection) during removal of spillages. Prevent entry into drains. Adsorb spillages with liquid-binding material (diatomite, universal binders, for small amounts of tissues). Do not adsorb onto sawdust or other combustible materials. Transfer to a container for disposal or recovery. Spillages or uncontrolled discharges into watercourses must be alerted to the appropriate regulatory body. |
| Waste disposal | Disposal should be in accordance with local, state, or national legislation. Incinerate under approved controlled conditions Decontaminate empty drums before recycling. |

SECTION IX • STORAGE AND HANDLING

| | |
|---|---|
| Storage | Keep in a cool, well ventilated place. Keep away from sources of ignition- No Smoking. Keep away from heat and direct sunlight. |
| Handling | Avoid contact with skin and eyes. Avoid inhalation of high concentration of vapors. Use in well ventilated area. The vapor is heavier than air; beware of pits and confined spaces. Take precautionary measures against static discharges. |
| Shipping classification DOT Hazard class | <ul style="list-style-type: none">• Dot Shipping Name: Methyl Methacrylate Monomer Stabilized.• TDG/UN Shipping Names: Methyl Methacrylate Monomer Stabilized• UN Number: UN1247• Hazard Class: 3• Packing Group: II• TDG Exemption: Not regulated.• Label: Corrosive Liquid• IATA Class: 3• IMDG Class: 3 |
| HMIS Coding | Health: 2 Flammability: 3 Reactivity: 2 |

SECTION X • ECOLOGICAL INFORMATION

| | |
|--|----------------|
| Environmental Fate and Distribution | Not available. |
| Persistence and Degradation | Not available. |
| Toxicity | Not available. |
| Effect of effluent treatment | Not available. |

SECTION XI • REGULATORY INFORMATION

• EC REGULATIONS:

TSCA STATUS: On Toxic Substance Control Inventory.
CERCLA REPORTABLE QUANTITY: Methyl Methacrylate, 1000 lbs (453.6 kg).
SARA TITLE III

- Section 302 : None
- Section 311/312: Acute, fire, chronic.
- Section 313: Methyl Methacrylate

RCRA STATUS: Methyl Methacrylate, U162

• CANADIAN REGULATIONS:

WHMIS Classification: B2 and D2B.

Anamet Inc. declines all warranties of description, merchantability or fitness for a particular purpose or any other warranties expressed or implied. All information contained in this data sheet result from figures supplied by the merchant and/or other recognized technical sources. Although this information is presumed to be complete and exact, Anamet Inc. does not guaranty any of the claims expressed or implied. Since the use of this product is not supervised by Anamet Inc., users are therefore responsible to verify if the product is designed for their particular application. They must also assume all risks associated with its use, manipulation and the elimination of the product as well as those arising from the publication, utilization or exactitude of the information contained in the present data sheet. This information pertains only of the product referred to in this specific data sheet and does not apply to its use in combination with other products or in any other process. In no event is Anamet Inc., will be liable for incidental or consequential damages resulting from the use or misuse of this product.



TERMINOLOGY

ACGIH: American Conference of Governmental Industrial Hygienists

CAS: Chemical Abstract Service

CFR: Code of Federal Regulations (Transportation in U.S.A.)

DOT: Department of Transportation (USA)

DSL: Domestic Substance List

IARC: International Agency for Research and Cancer

LC: Lethal Concentration

LD: Lethal Dosage

MSHA: Mine Safety and Health Administration (USA)

NIOSH: National Institute for Occupational Safety and Health (USA)

NTP: National Toxicology Program (U.S.A.)

OSHA: Occupational Safety and Health Administration (USA)

PEL: Permissible exposure limit.

STEL: Short term exposure limit.

TDG: Transportation of Dangerous Goods

TLV: Threshold limits value.

TSCA: Toxic Substances Control Act

TWA: Time-weighted average

USEPA: United States Environmental Protection Agency

WHMIS: Workplace Hazardous Materials Information System