MATERIAL SAFETY DATA SHEET • MSDS





SECTION 1 • PRODUCT IDENTIFICATION

TRADE NAME SILICON CARBIDE

ABRASIVE BELTS

ANAMET PRODUCT NUMBER 300-XXX

CHEMICAL NAME

MANUFACTURER / SUPPLIER'S NAME **ANAMET ADDRESS** P.O. Box 538

BOUCHERVILLE, QUÉBEC, J4B 6Y2

TELEPHONE NO. (450) 646-1290

EMERGENCY TELEPHONE NO. CANUTEC (613) 996-6666

SECTION II • COMPOSITION / INFORMATION ON COMPONENTS

Chemical characterization Description	CAS number	%	OSHA PEL (mg/m³)	ACGIH TLV (mg/m³)	
Silicon carbide.	409-21-2	15-45	Chemically inert.		
Backing, Polyester.	Not applicable.	20-65	Not Applicable.	Not Applicable.	
Bonding resin, Cured phenolic resin.	9003-35-4	5-20	Not Applicable.	Not Applicable.	
Respirable dust.	Not applicable.		15	10	
Total dust.	Not applicable.		15	10	

NOTE: Ingredients are listed on the TSCA Inventory of Chemical Substances. Those not identified are non-hazardous.

SECTION III • PHYSICAL / CHEMICAL CHARACTERISTICS

Boiling point in °C	Not Vapor pressure		Not	
Boning point in C	Applicable.	(mm Hg)	Applicable.	
Melting point in °C	Not	Vapor density (Air = 1)	Not	
	Applicable.		Applicable.	
Density	Not	Evaporation rate	Not	
(Water = 1)	Applicable.	(Butyl acetate = 1)	Applicable.	
Solubility in water	Insoluble.			
Appearance and odor	Sandpaper / Od	dorless.		







SECTION IV • FIRE	/ EXPLOSION HAZARD
-------------------	--------------------

Flash point	Not applicable	e.			
Flammable limits	LEL	Not	UEL	Not	
		applicable.		Applicable.	
Extinguishing medium	Water, carbon dioxide, foam and dry chemical.				
Special fire fighting procedures	Not applicable.				
Unusual fire and explosion hazards	Not applicable	Э.			

SECTION V • *REACTIVITY*

Stability	Stable.
Conditions to avoid	Avoid using product in totally unventilated area.
Incompatibility	Strong acids, strong bases, and strong oxidizing agents may
	modify the mechanical characteristics of the products and
	create safety hazards when used on machines.
Hazardous decomposition	In use, dust and decomposing odors may be generated. In
products	most cases, the material removed from the workplace will be
	significantly greater than the coated abrasives components.
Hazardous Polymerization	Will not occur.

SECTION VI • TOXICOLOGICAL PROPERTIES OF PRODUCT

A - SUGGESTED FIRST AID

Eyes	Immediately flush with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Get medical attention, if irritation or symptoms of overexposure persists
Skin	Immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
Inhalation	If dust from cutting or drilling is inhaled, remove the affected person to fresh air. If symptoms persist, get medical attention.
Ingestion	Accidental ingestion of this material is unlikely, If this does occur, watch person for several days to make sure intestinal blockage does not occur. If symptoms persist, call a physician.

iP'	orolot, ban a priyololari.
B - TOXICOL	OGICAL INFORMATION
	PRIMARY ENTRY ROUTES: Inhalation.
 SHORT TER 	RM EXPOSURE
Eyes	Dust May cause slight irritation.
Skin	Dust from this product may cause temporary mechanical irritation
Inhalation	Dusts from this product may cause mechanical irritation of the nose, throat

MATERIAL SAFETY DATA SHEET • MSDS





	and respiratory tract.						
Ingestion	Ingestion of this product is unlikely. However, ingestion of product may						
	produce gastrointe	produce gastrointestinal and disturbances.					
• LONG TERI	M EXPOSURE						
Carcinogenic	ity	None.					
		i					
_	y, Mutagenicity	None.					
Skin Sensitiz	roductive effects						
		None.					
Respiratory to	ract sensitization	Dust may slightly be irritating to the respiratory tract at high concentrations.					
Synergistic m							
Oyner gistic ii	MOTOR.						
SECTION V	II . DDECAUTION	NARY INFORMATION					
	PROTECTIVE MEA						
Eyes, face		Recommend standard face and eye protection at all times while using					
& hands	abrasive belts.						
Respiratory	As needed, use approved dust respirator (OSHA CFR1910.134)						
Ventilation	Do not use without adequate ventilation (OSHA 29CFR1910.94) (OSHA						
	29CFR1910.1000) (OSHA CFR1910.213) (OSHA 1910.243). Use adequate						
		anical exhaust ventilation.					
Hearing	As needed in accordance with OSHA 1910-215.						
HMIS Ratings		Health: 1 Fire: 0 Reactivity: 1					

Waste disposal

OLUTION IX	31011	IGE /	NIV IIAIL	LIIV	9				
Storage St	Store co	ated	abrasives	in ı	moderate	constant	t temperatur	e and	humidity
cc	onditions	S.							
Handling Be	Because	of th	e possibilit	ty of	abrasions	s use n	ormal hand,	face a	and body

SECTION VIII • SAFETY PRECAUTIONS IN CASE OF LEAKS OR SPILLS

Spill or leak procedure Use ordinary precautions for dusts and particulates.

Disposal should be in accordance with local, state, or national

legislation. Incinerate under approved controlled conditions.

Revised date: January 2015 SAFETY DATA SHEET / ABRASIVE BELTS - SILICON CARBIDE

SECTION IX . STOPAGE AND HANDLING





	protection.
Shipping classification DOT hazard class	 Dot Shipping Name: Not regulated. TDG/UN Shipping Names: Not regulated. UN Number: Not regulated. Hazard Class: Not regulated. Packing Group: Not regulated. TDG Exemption: Not regulated. Label: Not regulated. IATA Class: Not regulated. IMDG Class: Not regulated.
HMIS Coding	Health: 1 Flammability: 0 Reactivity: 1

SECTION X • ECOLOGICAL INFORMATION

Environmental Fate and Distribution	Not established.
Persistence and Degradation	Not established.
Toxicity	Not established.
Effect of effluent treatment	Not established.

SECTION XI • REGULATORY INFORMATION

EC REGULATIONS:

TSCA STATUS: On Toxic Substance Control Inventory.

CERCLA REPORTABLE QUANTITY: None.

SARA TITLE III

 Section 302: None. Section 311/312: None.

• Section 313: None.

RCRA STATUS: Not regulated.

CANADIAN REGULATIONS:

WHMIS Classification: Not regulated.

MATERIAL SAFETY DATA SHEET • MSDS





Anamet Inc. declines all warranties of description, merchantability or fitness for a particular purpose or any other warranties expressed or implied. All information contained in this data sheet result from figures supplied by the merchant and/or other recognized technical sources. Although this information is presumed to be complete and exact. Anamet Inc. does not guaranty any of the claims expressed or implied. Since the use of this product is not supervised by Anamet Inc., users are therefore responsible to verify if the product is designed for their particular application. They must also assume all risks associated with its use, manipulation and the elimination of the product as well as those arising from the publication, utilization or exactitude of the information contained in the present data sheet. information pertains only of the product referred to in this specific data sheet and does not apply to its use in combination with other products or in any other process. In no event Anamet Inc., will be liable for incidental or consequential damages resulting from the use or misuse of this product.



TERMINOLOGY

ACGIH: American Conference of Governmental Industrial Hygienists

CAS: Chemical Abstract Service

CFR: Code of Federal Regulations (Transportation in U.S.A.)

DOT: Department of Transportation (USA)

DSL: Domestic Substance List

IARC: International Agency for Research and Cancer

LC: Lethal Concentration

LD: Lethal Dosage

MSHA: Mine Safety and Health Administration (USA)

NIOSH: National Institute for Occupational Safety and Health (USA)

NTP: National Toxicology Program (U.S.A.)

OSHA: Occupational Safety and Health Administration (USA)

PEL: Permissible exposure limit.

STEL: Short term exposure limit.

TDG: Transportation of Dangerous Goods

TLV: Threshold limits value.

TSCA: Toxic Substances Control Act

TWA: Time-weighted average

USEPA: United States Environmental Protection Agency

WHMIS: Workplace Hazardous Materials Information System

Revised date: January 2015

SAFETY DATA SHEET / ABRASIVE BELTS - SILICON CARBIDE

Page 6 of 6