

MATERIAL SAFETY DATA SHEET • MSDS



SECTION 1 • PRODUCT IDENTIFICATION

TRADE NAME	ZIRCONIUM ALUMINA ABRASIVE BELTS
ANAMET PRODUCT NUMBER	320-XXX

CHEMICAL NAME

MANUFACTURER / SUPPLIER'S NAME ANAMET
ADDRESS P.O. Box 538
 BOUCHERVILLE, QUÉBEC, J4B 6Y2
TELEPHONE NO. (450) 646-1290
EMERGENCY TELEPHONE NO. CANUTEC (613)996-6666

SECTION II • COMPOSITION / INFORMATION ON COMPONENTS

Chemical characterization Description	CAS number	%	OSHA PEL (mg/m ³)	ACGIH TLV (mg/m ³)
Aluminum Oxide.	1344-28-1	15-30	15	10
Zirconium Oxide.	7440-67-7	15-30	5	5
Bonding resin.	Not established.	2-5	Not Applicable.	Not Applicable.

NOTE: Ingredients are listed on the TSCA Inventory of Chemical Substances. Those not identified are non-hazardous.

SECTION III • PHYSICAL / CHEMICAL CHARACTERISTICS

Boiling point in °C	Not Applicable.	Vapor pressure (mm Hg)	Not Applicable.
Melting point in °C	Not Applicable.	Vapor density (Air = 1)	Not Applicable.
Density (Water = 1)	Not Applicable.	Evaporation rate (Butyl acetate = 1)	Not Applicable.
Solubility in water	Insoluble.		
Appearance and odor	Sandpaper / Odorless.		

MATERIAL SAFETY DATA SHEET • MSDS



SECTION IV • FIRE / EXPLOSION HAZARD

Flash point	Not applicable.			
Flammable limits	LEL	Not applicable.	UEL	Not Applicable.
Extinguishing medium	Water, carbon dioxide, foam and dry chemical.			
Special fire fighting procedures	Not applicable.			
Unusual fire and explosion hazards	Not applicable.			

SECTION V • REACTIVITY

Stability	Stable.
Conditions to avoid	Avoid using product in totally unventilated area.
Incompatibility	Strong acids, strong bases, and strong oxidizing agents may modify the mechanical characteristics of the products and create safety hazards when used on machines.
Hazardous decomposition products	In use, dust and decomposing odors may be generated. In most cases, the material removed from the workplace will be significantly greater than the coated abrasives components.
Hazardous Polymerization	Will not occur.

SECTION VI • TOXICOLOGICAL PROPERTIES OF PRODUCT

A - SUGGESTED FIRST AID

Eyes	Immediately flush with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Get medical attention, if irritation or symptoms of overexposure persists...
Skin	Immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
Inhalation	If dust from cutting or drilling is inhaled, remove the affected person to fresh air. If symptoms persist, get medical attention.
Ingestion	Accidental ingestion of this material is unlikely, If this does occur, watch person for several days to make sure intestinal blockage does not occur. If symptoms persist, call a physician.

B – TOXICOLOGICAL INFORMATION

PRIMARY ENTRY ROUTES: Inhalation.

• SHORT TERM EXPOSURE

Eyes	Dust May cause slight irritation.
------	-----------------------------------

MATERIAL SAFETY DATA SHEET • MSDS



Skin	Dust from this product may cause temporary mechanical irritation
Inhalation	Dusts from this product may cause mechanical irritation of the nose, throat and respiratory tract.
Ingestion	Ingestion of this product is unlikely. However, ingestion of product may produce gastrointestinal and disturbances.

• LONG TERM EXPOSURE

Carcinogenicity	None.
Teratogenicity, Mutagenicity and other reproductive effects	None.
Skin Sensitization	None.
Respiratory tract sensitization	Dust may slightly be irritating to the respiratory tract at high concentrations.
Synergistic materials	None.

SECTION VII • PRECAUTIONARY INFORMATION PERSONAL PROTECTIVE MEASURES

Eyes, face & hands	Recommend standard face and eye protection at all times while using abrasive belts.
Respiratory	As needed, use approved dust respirator (OSHA CFR1910.134)
Ventilation	Do not use without adequate ventilation (OSHA 29CFR1910.94) (OSHA 29CFR1910.1000) (OSHA CFR1910.213) (OSHA 1910.243). Use adequate local and mechanical exhaust ventilation.
Hearing	As needed in accordance with OSHA 1910-215.
HMIS Ratings	Health : 1 Fire : 0 Reactivity : 0

SECTION VIII • SAFETY PRECAUTIONS IN CASE OF LEAKS OR SPILLS

Spill or leak procedure	Use ordinary precautions for dusts and particulates.
Waste disposal	Disposal should be in accordance with local, state, or national legislation. Incinerate under approved controlled conditions.

SECTION IX • STORAGE AND HANDLING

Storage	Store coated abrasives in moderate constant temperature and humidity conditions.
Handling	Because of the possibility of abrasions use normal hand, face and body protection.

MATERIAL SAFETY DATA SHEET • MSDS



Shipping classification
DOT
hazard class

- **Dot Shipping Name:** Not regulated.
- **TDG/UN Shipping Names:** Not regulated.
- **UN Number:** Not regulated.
- **Hazard Class:** Not regulated.
- **Packing Group:** Not regulated.
- **TDG Exemption:** Not regulated.
- **Label:** Not regulated.
- **IATA Class:** Not regulated.
- **IMDG Class:** Not regulated.

HMIS Coding

Health: 1 Flammability: 0 Reactivity: 0

SECTION X • ECOLOGICAL INFORMATION

Environmental Fate and Distribution	Not established.
Persistence and Degradation	Not established.
Toxicity	Not established.
Effect of effluent treatment	Not established.

SECTION XI • REGULATORY INFORMATION

• EC REGULATIONS:

TSCA STATUS: On Toxic Substance Control Inventory.
CERCLA REPORTABLE QUANTITY: None.
SARA TITLE III

- Section 302: None.
- Section 311/312: None.
- Section 313: None.

RCRA STATUS: Not regulated.

• CANADIAN REGULATIONS:

WHMIS Classification: Not regulated.

MATERIAL SAFETY DATA SHEET • MSDS

Anamet Inc. declines all warranties of description, merchantability or fitness for a particular purpose or any other warranties expressed or implied. All information contained in this data sheet result from figures supplied by the merchant and/or other recognized technical sources. Although this information is presumed to be complete and exact, Anamet Inc. does not guaranty any of the claims expressed or implied. Since the use of this product is not supervised by Anamet Inc., users are therefore responsible to verify if the product is designed for their particular application. They must also assume all risks associated with its use, manipulation and the elimination of the product as well as those arising from the publication, utilization or exactitude of the information contained in the present data sheet. This information pertains only of the product referred to in this specific data sheet and does not apply to its use in combination with other products or in any other process. In no event Anamet Inc., will be liable for incidental or consequential damages resulting from the use or misuse of this product.



TERMINOLOGY

ACGIH: American Conference of Governmental Industrial Hygienists

CAS: Chemical Abstract Service

CFR: Code of Federal Regulations (Transportation in U.S.A.)

DOT: Department of Transportation (USA)

DSL: Domestic Substance List

IARC: International Agency for Research and Cancer

LC: Lethal Concentration

LD: Lethal Dosage

MSHA: Mine Safety and Health Administration (USA)

NIOSH: National Institute for Occupational Safety and Health (USA)

NTP: National Toxicology Program (U.S.A.)

OSHA: Occupational Safety and Health Administration (USA)

PEL: Permissible exposure limit.

STEL: Short term exposure limit.

TDG: Transportation of Dangerous Goods

TLV: Threshold limits value.

TSCA: Toxic Substances Control Act

TWA: Time-weighted average

USEPA: United States Environmental Protection Agency

WHMIS: Workplace Hazardous Materials Information System